


# Pebble<sup>4</sup>

The color printer for plastic card personalization



Color & Monochrome Thermal Transfer



300 dpi



Single-sided



24 s/card



0.25 - 1 mm (10 - 40 mil)



3 years

**evolIS**

[www.evolis.com](http://www.evolis.com)

**Pebble<sup>4</sup> is designed to cater to all your requirements, be they small runs or bulk personalization of plastic cards. Pebble<sup>4</sup>, today, is the ideal solution for any type of application that requires single-sided printing of badges:** employee badges, student IDs, access control badges, transport passes, loyalty cards, payment cards and many more.

Thanks to the most advanced printing engine in the market, **Pebble<sup>4</sup>** delivers high-definition badges within seconds. This solution benefits from the latest encoding technologies: ISO or JIS2 magnetic tracks, and smart card with contact or contactless (RFID). These encoding options can be seamlessly combined to personalize multifeatured cards in a single pass.

**Pebble<sup>4</sup>** comes with a very convenient 100-card feeder. Yet, it can also turn into an elegant over-the-counter display, thanks to the manual feeding option that lets you print your badges, card by card, for instant delivery to the holder.

**Pebble<sup>4</sup>** comes in a splash of three different translucent colors that can be interchanged: switch from Fire Red to Jungle Green to Ocean Blue, and make sure **Pebble<sup>4</sup>** is always in line with your environment or taste.

The **Pebble<sup>4</sup>** range of printers proudly carries the stamp of Evolis' strong commitment to reliability, and therefore, benefits from unmatched quality along with a pioneering **3-year warranty**.

## GENERAL SPECIFICATIONS

- Color printing module
- 300 dpi print head (11.8 dots/mm)
- USB connection
- Option for Ethernet TCP-IP connection
- 16 MB RAM
- Detachable feeder with a capacity of 100 cards (0.76 mm - 30 mil)
- Output hopper with a capacity of 50 cards (0.76 mm - 30 mil)
- 1-Button and 4-LED control panel
- Printer colors: Ocean blue, Fire red or Jungle green

## PRINT MODES

- Color dye sublimation and monochrome thermal transfer
- Enhanced color management system for top quality pictures
- Edge-to-edge printing
- Integrated ribbon saver for monochrome printing

## PRINTING SPEED

Personalization throughput will depend on card design and printer settings

- Color (YMCKO): 150 cards/hour
- Monochrome: up to 1000 cards/hour<sup>1</sup>

## SUPPORTED PLATFORMS

- Windows™ XP, 2003 and Vista, 32 & 64 bits
- Mac™ OS X v10.2, 10.3 and 10.4
- Linux



## SOFTWARE SUPPLIED

- eMedia Card Designer Software for designing and editing badges
- Compatible with Windows™ XP, 2003 and Vista
- Connection to Microsoft™ Excel databases

## RIBBON TYPES

- 2-panel KO black monochrome ribbon - 500 cards/roll
- 5-panel YMCKO color ribbon - 200 cards/roll
- Half-panel YMCKO color ribbon - 400 cards/roll
- Monochrome ribbons - up to 1000 cards/roll (black, red, green, blue, white, gold and silver)
- Special ribbons:
  - Varnish hologram - 350 cards/roll
  - Scratch-Off - up to 1000 cards/roll

## OPTIONS

- Encoding options (can be combined):
  - Magnetic stripe encoder ISO 7811 HiCo/LoCo or JIS2
  - Smart contact station - ISO 7816-2
  - Smart contact station and encoding unit - PC/SC, EMV 2000-1
  - Contactless encoding unit - ISO 14443A, B, ISO 15693, Mifare, DesFire, HID iCLASS
  - Other types upon request
- 100-card additional feeder: Ocean, Fire and Jungle
- Manual card feeder: Ocean, Fire and Jungle
- Travel case
- Cleaning kits

## WARRANTY

Use Evolis Genuine products for best performance and extended lifespan of your printer

- Printer, print head: 3-year warranty, unlimited number of passes<sup>2</sup>

### Card types Card format

### Card thickness Card feeder capacity Card output hopper capacity Printer size Printer weight Connections Electrical Environmental

- All PVC, Composite PVC cards, PET, ABS<sup>1</sup> and special varnished<sup>1</sup> cards
- ISO CR-80 (53.98 mm x 85.60 mm - 3.375" x 2.125")
- ISO CR-79 (52.10 mm x 83.90 mm - 3.303" x 2.051") optional
- From 0.25 mm (10 mil) to 1 mm (40 mil)
- 100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
- 50 cards (0.76 mm - 30 mil), 150 cards (0.25 mm - 10 mil)
- Height: 192 mm (7.55") - Length: 396 mm (15.59") - Width: 235 mm (9.25")
- 5.9 Kg (13 lbs)
- USB (cable supplied) - Option for Ethernet TCP-IP
- Power supply: 110-230 Volts AC, 1.8 A, 60-50 Hertz - Printer: 24 Volts DC, 3 A
- Min/max operating temperature: 15° / 30° C (59° / 86° F)
- Humidity: 20% to 65% non-condensing
- Min/max storage temperature: -5° / +70° C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air

1. Under specific conditions.

2. Subject to observance of specific conditions and use of Evolis genuine consumables.



### EUROPE, MIDDLE EAST, AFRICA

#### Evolis Card Printer

29, Avenue de la Fontaine - Z.I. Angers Beaucoüzé  
49070 Beaucoüzé - France  
Tel: + 33 (0) 241 367 606 · Fax: + 33 (0) 241 367 612  
info@evolis.com

### AMERICAS

#### Evolis Inc.

1835 South Perimeter Road - Suite 190  
Fort Lauderdale - FL 33309 - USA  
Tel: (954) 491-9898 · Fax: (954) 491-5140  
evolisinc@evolis.com

### ASIA PACIFIC

#### Evolis Asia Pte Ltd

Centennial Tower, Level 21 - 3 Temasek Avenue  
Singapore 039190  
Tel: +65 6549 7606 · Fax: +65 6549 7001  
evolisasia@evolis.com

